

Thumb Shifter Road

Model No.		SLR96		SLR91		SLR80		
		R9	LF	R9	LF	R8	LF	8F
Speed	Rear	9-Speed	X	9-Speed	X	8-Speed	X	8-Speed
	Front	X	Friction (3 / 2)	X	Friction (3 / 2)	X	Friction (3 / 2)	Friction (3 / 2)
Mounting		(B) Bar End		(B) Brazed On Type 28.6mm / (C) Brazed On Type 44mm / (F) Brazed On Type 50mm		(B) Brazed On Type 28.6mm / (C) Brazed On Type 44mm / (F) Brazed On Type 50mm		(H) 22.2mm Clamp / (G) Handlebar Stem 25.4mm Clamp / (D) Down Tube 28.6mm Clamp
Shift Lever		Aluminum / High-Polished		Aluminum / High-Polished		Aluminum / High-Polished		Aluminum / High-Polished
Cable Type		Slick-Galvanized		Slick-Galvanized		Slick-Galvanized		Slick-Galvanized
Cable Length		2,400mm	1,900mm	1,950mm	1,450mm	1,950mm	1,450mm	R:1,950mm / L:1,450mm
Casing Compatibility		SP	SP	SP	2SP &↑	SP	2SP &↑	R: SP / L: 2SP &↑
Average Weight		105g	105g	50g	50g	50g	50g	(D) 107g / (G) (H) 122g

Model No.		SLR30				
		R7	R6	LF	7F	6F
Speed	Rear	7-Speed	6-Speed	X	7-Speed	6-Speed
	Front	X		Friction (3 / 2)	Friction (3 / 2)	
Mounting		(B) Brazed On Type 28.6mm / (C) Brazed On Type 44mm			(D) Down Tube 28.6mm Clamp / (G) Handlebar Stem 25.4mm Clamp / (H) 22.2mm Clamp	
Shift Lever		Aluminum			Aluminum	
Cable Type		Slick-Galvanized			Slick-Galvanized	
Cable Length		1,950mm		1,450mm	R:1,950mm / L:1,450mm	
Casing Compatibility		SP	2SP &↑	2SP &↑	R: SP / L: 2SP &↑	2SP &↑
Average Weight		50g	50g	50g	(D) 107g / (G) (H) 122g	

Thumb Shifter Road

Model No.		SLR03	
		FF	RF
Speed	Rear	Friction (8 / 7 / 6)	
	Front	Friction (3 / 2)	X
Mounting		(D) Down Tube 28.6mm Clamp / (H) Handlebar Stem 22.2mm Clamp	
Shift Lever		Aluminum	
Cable Type		Galvanized	
Cable Length		R:1,950mm / L:1,450mm	
Casing Compatibility		2SP & ↑	
Average Weight		(D) 78g / (H) 70g	(D) 45g / (H) 37g